

Velare™ BTM System – 14-3/4" wide Filler Cabinet

Mirrors	Velare
MasterFormat Section 10 28 13	
	<p>Technical drawing showing the dimensions and mounting details of the Velare BTM System Filler Cabinet. The cabinet is 23-1/4" wide [591] and 35-7/16" high [900]. It features a wall mounting hanger hook and security locking screws. Detail D shows edge clearance of 1/32" [0.8]. Detail B shows the bottom mirror mounting bracket with a screw #10 X 3/4" TYP and a plastic hole cap. Detail E shows the top mirror mounting bracket. A note indicates that all dimensions are in inches [mm].</p>
Scan for Information 	
SUSTAINABILITY/LEED	
MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)	

PRODUCT OVERVIEW

ASI's Velare™ Behind the Mirror (BTM) wall mounted type 304, alloy 18-8 stainless steel cabinet filler module provides spacing between other Velare™ BTM modules where needed. Mirror is made from 1/4" [6] thick frameless tempered glass conforming to ASTM C-1048 with pencil edges and eased corners with SS sheet intermediate stiffener and SS back plate with integral welded support mounts.

KEY FEATURES & SPECIFICATIONS

- Filler Cabinet designed for a more continuous look
- Fits adjacent to or between standard Velare™ cabinets
- Cabinet body is made of Type 304, alloy 18-8 stainless steel
- 1/4" [6] thick tempered glass mirror has a pencil edge with a radius for safety and elegance
- Surface Mounted
- 23-1/4" [591] Wide

**TECHNICAL INFORMATION / PRODUCT PROPERTIES**

Property	Value
Dimensions	23-1/4" [591] W x 35-7/16" [900] H x 7-9/16" [192] D
Construction	Type 304, alloy 18-8 stainless steel - Satin Finish Frame 1/4" [6.4] thick tempered glass mirror has a pencil edge with a radius for safety and elegance
Mounting	Surface Mounted
Materials	<u>Cabinet:</u> 14, 16, 18, 20 and 22 gauge type 304, alloy 18-8 stainless steel. <u>Glass</u> Tempered glass

INSTALLATION

Mount cabinet on wall using twelve (12) #12 self-threading pan-head screws (by others) through two (2) concealed mounting plate into appropriate anchoring and wall reinforcement and hang unit on hooks on mounting plate. Install two (2) #12 self-threading locking screws (by others) into appropriate anchoring to prevent unit from being lifted off hanger hooks. Position mirror in front of cabinet and insert top and bottom rear tabs into receiver-slots. Secure mirror with two (2) #10-32x3/4" Pan Head screws (provided) to the bottom mirror mounting brackets through the bottom access holes by engaging and securing to threaded inserts provided on bottom mirror rear mounting tabs. Cover the screw access holes using the two (2) black plastic hole caps (supplied). Suggested mounting height is to position bottom of module 16" to 20" [508] above vanity top so bottom aligns with ASI models 0661-X or 0663-X on either side of Filler Module. See complete IG before starting installation.

SIZE OPTIONS**GLAZING OPTIONS**

Not Available

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #0661-FM-23

Revision: R2 Issued: 11/1/2021 Revised: 4/15/2025

CSI:10 28 13 Toilet Accessories

Page: 2 of 2

Manufacturer reserves the right to make changes to the design, dimensions or functionality of the product without formal notice.